

# METAPACE



- Cordless bar code scanner with Bluetooth interface
- High-performance linear imager - high-speed scanning of 1D and GS1 bar codes
- Huge memory for up to 32,000 scans while in Batch mode
- Up to 90 m transfer distance - enormous range thanks to Bluetooth class 2
- BT cradle included - flexible use as handheld or presentation scanner
- Highly reliable - no moving parts and sturdy housing

## Specifications

<b>Connectivity</b>	BT Class 2 (2.4 GHz) Version 2.0
<b>Range</b>	Up to 90 m / 295 ft. line of sight
<b>Category</b>	BT linear imager
<b>Resolution</b>	3 mil
<b>Depth of field (depends on bar code resolution)</b>	0.5 to 35 cm 0.2 to 13.8 in.
<b>Scanning angle</b>	Pitch: $\pm 70^\circ$ , skew: $\pm 70^\circ$
<b>Scan rate</b>	200 scans/second, 200 decodes/second
<b>Interface</b>	USB
<b>Hands-free scanning</b>	Auto-sense and continuous modes
<b>Supported bar codes</b>	Codabar, Code 39, Code 93, Code 128, GS1 Databar (RSS), Industrial 2 of 5, Interleave 2 of 5, Italian and French Pharmacodes, Matrix 2 of 5, MSI, Plessey, RSS14, Telepen, UPC/EAN/GS1-128, and more
<b>Language support</b>	English, French, Italian, Belgian, Norwegian, Swedish, Portuguese, German
<b>Weight</b>	173 g / 6.1 oz.
<b>Voltage</b>	+5V $\pm$ 10%
<b>Temperature</b>	Operating: 0° to 50°C / 32° to 122°F Storage: -20° to 60°C / -4° to 140°F
<b>Humidity</b>	Operating, non-condensing: 10% to 90% Storage, non-condensing: 5% to 95%
<b>Impact resistance</b>	1.2 m / 3.9 ft. multiple drops onto concrete
<b>Ingress protection</b>	IP30
<b>Configuration</b>	Setup using Windows-based Metapace ScanMaster software (included), by direct connection, or printed bar codes
<b>Accessories</b>	3-way desk / wall / auto-sense stand with weighted base, providing BT communication for up to seven scanners
<b>Warranty</b>	3 years (except battery)



Your Dealer

Subject to change without notice.

www.metapace.com