

CUSTOMER DISPLAY

Model C2202-P D

CITIZEN

Micro HumanTech

Leading Technology for Humanity




C2202-PD

Included items

- Display unit
- Base unit
- Short pole
- Long pole
- AC adapter
- AC cable
- Interface cable
(DB25 female ♂DB9 male)
- User's manual

Connector layout of base unit



Specifications

Display method	Vacuum fluorescent display
Display color	Blue green
Number of character	20 columns x 2 lines
Brightness	700cd/m ²
Character font	5 x 7 dot matrix, comma, decimal point
Character size(W x H)	5.25 x 9.2mm
Character pitch	8.3mm
Code page	PCⒹ437/850/860/863/865, Slavonic, Russian, Katakana
Emulation	CBM standard, ESC/POS*
Interface	RSⒹ232C (with path through function)
Power supply	12V DC
Power consumption	4.5W
MTBF	25,000 hours
Dimensions (W x H x D)	230 x 100 x 42mm
Viewing angle	±30 degrees
Rotation angle	Maximum 270 degrees
Weight	0.9kg
Safety standard	FCC class B, CE marking

CITIZEN SYSTEMS JAPAN CO.,LTD.

OVERSEAS SALES DEPT., SALES DIVISION :
6-1-12, TANASHI-CHO, NISHI-TOKYO-SHI, TOKYO 188-8511, JAPAN
Tel.(81)-424-68-4608 Fax.(81)-424-68-4996
<http://www.citizen-systems.co.jp>
e-mail : sales-op@systems.citizen.co.jp

CITIZEN IS A REGISTERED TRADEMARK OF CITIZEN WATCH CO., LTD., JAPAN

All specifications are subject to change without prior notice.

All trademarks or registered trademarks are the property of their respective owners.

(Rev.:2006.08)