

Glancetron GT15plus LCD monitor with integrated touch screen



- High-End 38.1 cm (15") LCD monitor for demanding applications
- Integrated touch screen with 5-wire resistive touch technology
- Extremely elegant design and especially robust construction
- Dual: touch screen interface with RS232/USB and AC/DC voltage supply
- Maximum resolution: 1,024 x 768 pixels

Specifications

| | | |
|--------------------|------------------------------|--|
| General | Model | GT-15 plus |
| | Colour | Dark Grey |
| | Dimensions | 321.9 x 364 x 206.08 mm (H x W x D) |
| | Net Weight / Shipping Weight | 5.0 kg / 7.9 kg |
| | Power Supply | AC Input 90 ~ 264 V / DC 12 V |
| | Power Consumption | Operating: 25W (typ.) / Sleep: 4W / Off: 2W |
| Display | Mounting Option | Stand / 75 x 75 mm VESA Mount |
| | LCD Size / Type | 15 Inch TFT Active Matrix Panel |
| | Active Area | 304 x 228 mm (H x V) |
| | Pixel Pitch | 0.297 x 0.297 mm (H x V) |
| | Panel Resolution | 1,024 x 768 Pixels |
| | Display Mode | VGA 720 x 400 (70Hz) |
| | Display Colour | 16.2 Million Colours |
| | Contrast | 500:1 |
| | Brightness | Without Touch 250 nits / SAW 230 nits / Capacitive 212 nits / Resistive 200 nits |
| | Response Time | Tr: 2 ms / Tf: 6 ms |
| | Viewing Angle | Horizontal: 70° ~ -70° / Vertical: 65° ~ -60° |
| | Video Input Format | RGB Analog 0.7 Peak to Peak |
| | Video Sync Format | Separated H&V Sync. / Composite Sync. / Sync-on Green |
| | Video Input Frequency | Horizontal: 31Khz ~ 60.2 kHz / Vertical: 56 Hz ~ 76 Hz |
| Video Signal Input | D.sub 15 pin Female (Analog) | |
| Environment | Temperature - Operating | 0°C ~ +40°C |
| | Temperature - Storage | -20°C ~ +60°C |
| | Control Key | Power On/Off, Select, Down, Up, Menu |
| | Audio | 1W Speaker / 2 Channels |



Your Dealer